



Ref. No.	Part Number	Description	DEF		
1	306-11310-01-00	CYLINDER (306-11311-01).....	1	1	1
2	91830-24016-00	PIN, dowel (10.5-14-16) (91800-16016).....	4	4	4
3	90116-10108-00	BOLT, stud (256-11361-00).....	8	8	8 M
4	93210-82153-00	O-RING (1.5-81.5).....	2	2	2
5	256-11351-01-00	GASKET, cylinder 1 (256-11351-00).....	1	1	1
6	306-11181-00-00	GASKET, cylinder head.....	1	1	1
	2F0-00000-20-00	GASKET KIT.....	1	1	1 S Kit
7	97321-08035-00	BOLT, hexagon.....	2	2	2
8	92903-08200-00	WASHER, plain.....	2	2	2
9	97313-06035-00	BOLT, hexagon (97323-06035)	1	1	1
10	92903-06200-00	WASHER, plain.....	1	1	1
11	256-11395-02-00	HOLDER.....	2	2	2
12	90430-11033-00	GASKET (256-11397-01).....	2	2	2

XS650D

Bore x Stroke x Cylinder(s)	Displacement	75 x 74mm x 2	653cc (39.85 CID)
Compression Ratio	(pressure)	8.4:1	

XS650E

Bore/Stroke/Number Cylinders/Displacement (cc)	75mm / 74mm / 2 / 653cc
Compression Ratio/Compression Pressure min. ~ max.	8.5:1 / 128 ~ 156 psi

XS650F

ENGINE TYPE	4-Stroke, SOHC, Air-Cooled
Bore/Stroke/Number Cylinders/Displacement (cc)	75mm / 74mm / 2 / 654cc
Compression Ratio/Compression Pressure min ~ max	8.5:1 / 9.5 ~ 11.5 kg/cm ²